

libretools - Bug #1323

[librechroot]->mkarchroot->pacstrap uses system pacman.conf by default

2017-05-09 09:57 PM - lukeshu

Status: open	% Done: 0%
Priority: bug	
Assignee:	
Category:	
Description	
<pre><fauno> ==> Creating 'root' copy for chroot [default] <fauno> ==> Creating install root at /var/lib/archbuild/default/root <fauno> [...] <fauno> error: failed retrieving file 'repo.db' from disk : Couldn't open file /var/lib/archbuild/default/fauno/repo/repo.db <fauno> error: failed to update repo (download library error) <fauno> [...] <fauno> Enter a selection (default=all): error: failed to prepare transaction (could not find database) <fauno> [...] <fauno> ==> ERROR: Failed to install packages to new root <fauno> ==> ERROR: Failed to install all packages <fauno> libretools should use a vanilla pacman.conf <lukeshu> it mostly does <fauno> it used my systemd pacman.conf <fauno> which is heavily modified <fauno> it's working now i removed [repo]</pre>	
Perhaps it should default to -A \$CARCH. But at least it should use the /usr/share/pacman/defaults/ pacman.conf for pacstrap.	
Related issues:	
Related to libretools - Bug #501: [RFC] [libremakepkg]Uses the chroot makepkg... info needed 2014-02-22	

History

#1 - 2018-08-16 12:06 AM - lukeshu

- Related to Bug #501: [RFC] [libremakepkg]Uses the chroot makepkg.conf when downloading sources added